

FEATURES

- o Customised shape according to your project.
- o Fully homogeneous and uniform diffuser appearance.
- o Stainless steel, aluminium, brass and copper finishes.
- o Range of light outputs available.
- o Surface mounted, flush recessed and plaster-in variations.
- o 50,000+ hours life expectancy.
- Emergency lighting with 3 hour operation.
- o IP44 up to IP68 protection available.
- o Diffuser customisations and optics available.
- Wide selection of controls options.
- Luminaire output up to 10,000 lm/m2.

TECHNICAL INFO





EXAMPLE ORDER CODE

FAB-B-X-SITE-SITE-SITE-55-44-2700-FA-RA-CL-SWITCHED

DIM A	DIM B	DIM C	OUTPUT	IP RATING	LIGHT COLOUR	DIFFUSER	FINISH	MOUNTING	CONTROL
SITE	SITE	SITE	55	44	2700	Frosted Acrylic - FA	Raw Aluminium - RA	Clips - CL	Switched
			110	65	3000	Opal Acrylic - OA	Anodised Silver - AS	Recessed Box - RB	Dali
			165	67	4000	Dark Acrylic - DA	Anodised Black - AB	Suspended - S	DMX
				68	5000	Opal Glass - OG	Anodised Colour - ARAL		Art-Net
					RGB		Powder Coat White - PW		Fab Content
					RGBW		Powder Coat Black - PB		
					RGBWW		Powder Coat Colour - PRAL		
					RBGCW/WW		Stainless Steel - SS		
							Brass - BR		
							Copper - CO		



