



SURFACES LIGHTBOX ROUND



FEATURES

- Fully homogeneous and uniform diffuser appearance.
- Connect or abut fixtures with seamless light.
- Stainless steel, aluminium, brass and copper finishes.
- Range of light outputs available.
- Surface mounted, flush recessed and plaster-in variations.
- 50,000+ hours life expectancy.
- IP44 up to IP68 protection available.
- Diffuser customisations and optics available.
- Wide selection of controls options.
- Luminaire output up to 10,000 lm/m².

TECHNICAL INFO



EXAMPLE ORDER CODE

FAB-B-ROU-100-50-55-44-2700-FA-RA-CL-SWITCHED

DIM A	DIM C	OUTPUT	IP RATING	LIGHT COLOUR	DIFFUSER	FINISH	MOUNTING	CONTROL
Min 100	Min 50	55	44	2700	Frosted Acrylic - FA	Raw Aluminium - RA	Clips - CL	Switched
150	100	110	65	3000	Dark Acrylic - DA	Anodised Silver - AS	Recessed Box - RB	Dali
200	150	165	67	4000	Opal Glass - OG	Anodised Black - AB	Suspended - S	DMX
500	200		68	5000		Anodised Colour - ARAL	In-ground - ING	Art-Net
1000	300			RGB		Powder Coat White - PW		Fab Content
SITE	SITE			RGBW		Powder Coat Black - PB		
				RGBWW		Powder Coat Colour - PRAL		
				RGBCW/WW		Stainless Steel - SS		
						Brass - BR		
						Copper - CO		